



# Rhino™

## RhinoPro™ HP-21 Classic

### High Pressure Proportioning Unit

with 10.2 kw of Heating Power  
for Polyurethane/Urea Systems



ISO 9001:2000  
FM62236

#### MACHINE SPECIFICATIONS

- Output:** 5 – 12 lbs/min
- Max Operating Pressure:** 2000 PSI
- Electrical:** 240 VAC; 3 PH; 50 AMP or 240 VAC; 1 PH; 75 AMP
- Primary Heaters:** 10.2 KW with individual controls
- Weight:** 438 lbs
- Dimensions:** 46" H x 31" W x 32" D
- Heated Hoses:** 50 to 200 feet plus 10 ft. whip



RhinoPro™ HP-21 Classic

The RhinoPro™ HP-21 Classic is a high performance plural component spray machine specially designed to process Rhino Linings® protective lining systems for truck beds and light industrial jobs under 5000 sq. ft. It is capable of generating 2000 psi spray pressure to accurately mix and spray fast-setting systems. The HP-21 Classic offers a number of advantages including:

- On/Off trigger capability allows the ability to spray small or intricate parts or thinner coats
- Ability to control output and spray pattern with various gun configurations.
- Data recorder (optional) offers real-time data capture of process parameters to verify that the chemicals were sprayed at the proper conditions.
- Compact, portable wheeled cart allows you to move the unit closer to the job and occupies less space.
- Primary heaters allowing for quick startup times with urethane/urea systems.

#### SUPERIOR EFFICIENCY OF ELECTRIC MOTORS

Improves performance and reduces operating costs

#### PRESSURE BALANCE VALVES

Offer quick and easy balancing of system pressures

#### ELECTRIC HEATED HOSE AND WHIP HOSES

Moisture resistant and can be extended to 210 feet

#### EASY-TO-USE FUSION SPRAY GUN

Offers superior mix quality, less maintenance and downtime, easy clean-up and longer component life

#### HIGH OUTPUT HEATER(S)

Maintain chemical temperatures with up to 10,200 watts of energy

# RhinoPro™

## HP-21 Classic

### High Pressure Proportioning Unit

#### MACHINE SPECIFICATIONS

**Output:** 5 – 12 lbs/min  
**Max Operating Pressure:** 2000 PSI  
**Electrical:** 240 VAC; 3 PH; 50 AMP or 240 VAC; 1 PH; 75 AMP  
**Primary Heaters:** 10.2 KW with individual controls  
**Weight:** 438 lbs  
**Dimensions:** 46" H x 31" W x 32" D  
**Heated Hoses:** 50 to 200 feet plus 10 ft. whip

#### ■ EQUIPMENT/PROCESSING

RhinoPro™ HP-21 Classic delivery system  
Spray gun complete with mix modules & spray tips  
Transfer pumps & recirculation assembly  
50 ft Heated hose  
10 ft Heated whip hose  
Drum agitator assembly  
Air desiccant dryers  
RhinoPro™ Membrane Dryer\*

#### ■ SAFETY PACKAGE\*

Protective apparel  
Air respirator pump and hoses (two person)  
Full face mask and loose-fitting hood  
Air pump filters (exhaust and intake)

#### ■ ACCESSORIES\*

Spare parts for spray gun  
Technical & Safety manuals  
Required tools  
Gram scale  
Drum dolly

#### ■ TRAINING\*

Comprehensive training

**NOTE:** \*Items are sold separately to existing dealerships. Pricing subject to change without notice. Freight & build-out not included. Chemical components not included. The above is a breakdown of the major components and is not the complete list of supplied materials.

©Rhino Linings Corporation. All rights reserved.



 **Rhino Linings®**  
**Rhino Linings Corporation**  
9151 Rehco Road, San Diego, CA 92121  
858-450-0441 • Fax 858-450-6881  
1-800-422-2603  
[www.rhinolinings.com](http://www.rhinolinings.com)

Rhino Linings Australasia Pty Ltd ..... +61 7 5585 7000  
(Asia and Australia)  
Rhino Linings Canada, Inc ..... 1-866-447-1471  
Rhino Linings Europe ..... +49 6103 936474  
(Africa, Europe and Middle East)  
Rhino Linings Latin America ..... +52 55 5632 0195  
(Mexico, Caribbean, Central and South America)